

**SCHEDA TECNICA N°17**

SCIK ANTIMACCHIA

Odourless, anti-smoke, stain-resistant paint

DESCRIPTION

SCIK ANTIMACCHIA INODORE is a matt paint for interior walls, designed to cover and block recurrent stains caused by smoke, soot, coffee, nicotine and tar, thanks to the odorless solvents, which significantly improve working conditions.

The product is particularly suitable for the treatment of humid premises such as bathrooms, kitchens, cellars, etc.

The high water-resistant quality and the anti-molds properties of this product, combined with the excellent breathability, makes SCIK ANTIMACCHIA ODORENT applicable on any type of substrate such as plasters, concrete, plaster, wood, plasterboard, chipboard and old paint.

APPLICATION

Wall, gypsum, plasterboard:

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- Remove any layers of old paint or imperfectly anchored parts and sand the entire surface.
- Level out imperfections with STUCCO TRE STELLE or smooth out support irregularities with RASAN STUCCO o con K-STUCC.
- Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.
- Treat the surface with SCIK BONIFIK in case of mold.
- Make sure the surface is dry and apply 1 coat of SCIK PURAL ACRIL insulation or FISSATIVO ACRILICO TRE STELLE; in case of flaking or old paint with low thickness presence, apply 1 coat of fixative insulating agent to the solvent PRIMER CONSOLIDANTE on internal or external surfaces.
- Proceed applying with brush or roller 2 coats of SCIK ANTIMACCHIA INODORE which has to be thinned up with DILUENTE ISOSOL INODORE (check technical data sheet n°144) in the following percentages: approx. 5-10%.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273


P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Acrylic, synthetic resins in solution
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Diluyente 10-15%
Yield	10-12m ² /Lt
Specific weight	1,433Kg/Lt
Colors	White
Dry aspect	Matt
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Diluyente inodore
Packing	15LT,5LT,0,750LT

CHARACTERISTICS

Characteristics:	Linea Scik.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush,Sprayer.
Related products:	STUCCO TRE STELLE,RASAN STUCCO,K-STUKK,SCIK BONIFIK,SCIK PURAL ACRIL,FISSATIVO TRE STELLE.

- Avoid contact with skin and eyes.
- In case of eye contact rinse thoroughly with plenty of water and consult a doctor.
- Wear protective gloves/ eye protection/ face protection when using the product.
- Do not inhale.
- Keep out of reach of children.

Use the product in accordance with the relevant health and safety regulations of the country.

Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste.

For further information please refer to **SSR17** safety data sheet.

ITEM SPECIFICATION

Odourless, anti-smoke, stain-resistant paint. Applications to be made on already prepared surfaces of SCIK ANTIMACCHIA INODORE cod.SAI01 based on odourless solvent and acrylic resins, at least into 2 layers, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com