

## **TITAN LAVABILE**

Washable water-based paint, for internal and external

### **DESCRIPTION**

TITAN LAVABILE is a washable water-based paint, designed for giving an excellent wash resistance and a good whiteness point to the substrate.

Easy to apply and particularly suitable for protection and decoration of interior surfaces, where a high level of finish is required.

### **APPLICATION**

#### **New Walls:**

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster.
- Level out imperfections of the internal support with RASAN STUCCO (check technical data sheet 48) or with K-STUKK (check technical data sheet 48a); use instead RIVENDUIT CALCE for the external support (check technical data sheet 48b). In case of holes or micro-cracks, fill the inner walls with STUCCO TRE STELLE (check technical data sheet n° 33).
- Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.
- Treat the surface with SCIK BONIFIK (check technical data sheet n° 146) in case of mold.
- Make sure the surface is dry and apply 1 coat of SCIK PURAL ACRIL insulation (check technical data sheet n°118) or FISSATIVO ACRILICO TRE STELLE (check technical data sheet n°51).
- Proceed applying two coats of TITAN LAVABILE with brush, roller or spray, which has to be thinned up with water in the following percentages: 1st coat: approx.25-30% ; 2nd coat: approx. 20-25%.

#### **Old Walls:**

- The surface to be treated must be dry.
- Scrape off any loose flaking and poorly adhering coating, scraping and washing the surface with plenty of water or using a pressure washer.
- Proceed following the instruction of 'NEW WALLS' from the third point onwards.

## TECHNICAL DATA

Nature of the bond	Vinyl-versatate copolymer in aqueous solution
Viscosity	32000 cps $\pm$ 1600 a 30°C (viscosimetro rotazionale Brookfield)
Drying Time	6-12 h complete.
Thinning	25-30% 1°mano Water;20-25% 2°mano Water
Yield	10-12m <sup>2</sup> /Lt
Specific weight	1,601Kg/Lt
Colors	White or colored upon request with RIVEDIL COLOR system
Dry aspect	Matt
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	$\mu$ Gr/m <sup>3</sup>
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	4LT,14LT

## CHARACTERISICS

Characteristics:	Idropittura,Washable,Opaco.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

## TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush.
Related products:	.

### SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR25** safety data sheet.

### ITEM SPECIFICATION:

Super washable water-based paint for internal and external. TITAN LAVABILE cod.TL,based on vinyl-versatic resins in aqueous dispersion and mineral fillers for internal and external. Applications of washable water- based paint made on already prepared surfaces, at least into 2 layers, determined in quantities by the substrate absorption. Supply and installation of material € ..... per sqm.

### NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

colorificio  
**Rivedil**  
made in Italy

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com