

**SCHEDA TECNICA N°33****STUCCO TRE STELLE**

Plasters for indoor/outdoor

DESCRIPTION

Ideal for plastering and restoring surfaces such as walls, frames, rose window, plasterboard, etc., STUCCO is presented as an interior filler.

The product is indicated to level support irregularities, such as small cracks or slight depressions.

Once applied, STUCCO TRE STELLE can be sanded.

APPLICATION

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- Remove by brushing or by washing any granules and efflorescences from plaster.
- Level out imperfections of the internal support with RASAN STUCCO (check technical data sheet 48) or with K-STUKK (check technical data sheet 48a). In case of holes or micro-cracks, fill the inner walls with STUCCO TRE STELLE (check technical data sheet n° 33).
- Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	N/A
Viscosity	
Drying Time	12-24 h complete.
Thinning	
Yield	secondo diluizione e supportom ² /Kg
Specific weight	1/5Kg/Lt
Colors	White
Dry aspect	Mellow
Wet aspect	Mellow or powder
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	μGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	1KG,5KG

CHARACTERISTICS

Characteristics:	Riempitivo.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Stainless Steel Trowel 200x80cm,Stainless Steel Trowel 240x100cm.
Related products:	.

SAFETY INSTRUCTIONS:

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR76** safety data sheet.

ITEM SPECIFICATION:

Plaster for internal and external. Applications of water plaster for rose windows and frames with special powders, made on already prepared internal surfaces, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com