

**SCHEDA TECNICA N°51**

FISSATIVO TRE STELLE

Water-based acrylic insulation for internal and external

DESCRIPTION

FISSATIVO TRE STELLE is an acrylic insulation with the aim of making the following wall supports suitable for painting: new plasters, crumbling wall surfaces, pre-painted wall with layers of old paint and plastered wall.

The main purpose is to improve the cohesion and standardize the support absorption in order to create the ideal anchorage for the next layer of paint.

The upgraded product formula increases painting performance and allows paint layer insulation from wall surface acidity.

APPLICATION

Wall, gypsum, plasterboard:

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- Remove any layers of old paint or imperfectly anchored parts and sand the entire surface.
- In case of holes or micro-cracks, fill the inner walls with STUCCO TRE STELLE (check technical data sheet n°33) and level out imperfections of the internal support with RASAN STUCCO (check technical data sheet 48) or with K-STUKK (check technical data sheet 48a), use instead ESTERN STUCCO to level out imperfections (check technical data sheet n° 76) for the external support or RIVENDUIT CALCE (check technical data sheet 48b).
- Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.
- Make sure the surface is dry and proceed applying with brush or roller 1 coat of FISSATIVO ACRILICO TRE STELLE (check technical data sheet n°51), which has to be thinned up with water : add in 1lt of product up to 5lt of water as required.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273


P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Acrylic copolymer in water dispersion
Viscosity	
Drying Time	1 h at touch, 6-12 h complete.
Thinning	Water 1:5 MAX
Yield	15-20m ² /Lt
Specific weight	0,95Kg/Lt
Colors	Colourless
Dry aspect	Colourless
Wet aspect	Colourless
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	0,750LT,5LT,15LT

CHARACTERISTICS

Characteristics:	Isolante.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	.
Related products:	.

SAFETY INSTRUCTIONS:

Use the product in accordance with the relevant health and safety regulations of the country.
Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste.
For further information please refer to **SSR51** safety data sheet.

ITEM SPECIFICATION:

Water-based acrylic insulation for internal and external. FISSATIVO ACRILICO TRE STELLE cod.FS, suitable for consolidating and insulating wall supports determined in quantities by the substrate absorption. Applications made on already water- based insulation prepared surfaces. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com