

SCHEDA TECNICA N°55

RAPID FLATTING

Quick-drying gloss-transparent varnish for wood

DESCRIPTION

RAPID FLATTING is a quick-drying product with a gloss transparent effect, designed for painting interior and exterior wooden items.

The product, based on synthetic resins and nitrocellulose, offers good expansion and fullness.

RAPID FLATTING emphasizes the natural beauty of wood grain, following the structural variations, typical of the material.

APPLICATION

NEW WOOD SURFACES:

- · Sand to remove any raised wood flakes.
- The substrate has to be well prepared and suitable for coating, so make sure the wood is not damp.
- · Level out imperfections with PASTA STUCCO.
- · Sand the grouting and then eliminate dust deposits.
- After 6-12 hours, proceed with the support impregnation treatment using IMPRELEGNO or IMPRECOLOR.
- Lightly sand the surface and apply with brush or spray, 1 or 2 coats of RAPID FLATTING, which has to be thinned up with DILUENTE SINTETICO or DILUENTE NITRO, in the following percentages: approx 5 -10%.

Pre-PAINTED WOOD SURFACES:

- Verify the condition of the old paint. Scrape off any loose flaking and poorly adhering coating.
- Proceed as for the new wood surfaces from second point onwards



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy Tel. (+39) 0832 731293 - (+39) 0832 731273 P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	synthetic resins
Viscosity	
Drying Time	2 h at touch, 4-6 h complete.
Thinning	Diluente sintetico 10-15%
Yield	8-10m²/Lt
Specific weight	0,900Kg/Lt
Colors	gloss transparent
Dry aspect	gloss transparent
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	years (in sealed, unopened original packing)
voc	μGr/m³
TVOC	N/A
PH	N/A
Cleaning	Diluente sintetico
Packing	2,5LT,0,750LT
CHARACTERISTICS	
Characteristics:	Linea legno.
Can be applied on:	Wood.
for:	Interiors ed Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Brush,Sprayer.
Related products:	PASTA STUCCO,IMPRELEGNO,IMPRECOLOR,DILUENTE NITRO,DILUENTE SINTETICO.

SAFETY INSTRUCTIONS:

Harmful and flammable product:

- Keep away from heat, sparks and open flames No smoking.
- Avoid contact with skin and eyes.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

If swallowed, do NOT induce vomiting: immediately consult the doctor showing the product label or the container.

Keep out of reach of children. Avoid release to the environment, as toxic. Do not empty into drains or the aquatic environment. For further information, please consult the **SSR55** safety data sheet.

ITEM SPECIFICATION:

Quick-drying gloss-transparent varnish for wood. Applications to be made on already prepared surfaces of quick-drying gloss-transparent varnish for wood RAPID FLATTING cod. RFG01, based on special resins, in 2 layers at least, in quantities determined by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy Tel. (+39) 0832 731293 - (+39) 0832 731273 P.IVA 01122590753

www.rivedil.com - export@rivedil.com