

SCHEDA TECNICA N°68

MURAL 3

Wall protection product, water-based, consolidating, acrylic, water repellent

DESCRIPTION

MURAL 3 is a wall protection product composed of solvent- based acrylic resins, designed as a barrier for internal and external support, particularly subject to the erosive action of water or exposed to atmospheric agents.

The product has excellent water-repellent and washable properties, infact it prevents water from penetrating into the substrate.

In addition, besides protecting the support, MURAL1 brightens the colour giving it a glossy appearance.

MURAL 3 can be applied on different types of visible surfaces, such as plastic coatings, paints, carparo, tufa stone, etc.

APPLICATION

Plastic coatings, paints, carparo, tufa stone surfaces:

- Brush the surface, in order to remove any loose leaf flakes and ensure that surface crusts and traces of dirt are cleaned up.
- In the presence of molds, treat the surface with SCIK BONIFIK.
- Make sure the surface is dry and with a brush, roller or spray proceed applying 1 or 2 coats of MURAL 3 ready to use.

PLEASE NOTE:

For external application during winter time, it is advisable not to use the product in presence of high atmospheric humidity or wet surfaces. Please avoid the application with probable chance of rain within 48 hours, which could cause the whitening of the support.

We also advise to protect the floors and to ensure the complete evaporation of the product before staying in the treated environment.



TECHNICAL DATA	
Nature of the bond	Styrene-acrylic copolymers in aqueous dispersion
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	6-8m²/Lt
Specific weight	0,957Kg/Lt
Colors	transparent glossy
Dry aspect	transparent glossy
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
voc	μGr/m³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	15LT,5LT,0,750LT
CHARACTERISICS	
Characterisics:	Linea idrorepellenti.
Can be applied on:	Walls, Wood.
for:	Interiors ed Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Brush,Sprayer.
Related products:	SCIK BONIFIK.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates.

Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR68** safety data sheet.

ITEM SPECIFICATION:

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.

