

LESION STUCCO

Stucco based on elastic compound in paste form

DESCRIPTION

LESION STUCCO is a stucco based on elastic compound in paste form, used for internal and external supports.

The product has been designed to seal injuries due to construction settlements and expansion points caused by temperature changes.

The proven elasticity of the filler allows to uniform and level the treated surface, penetrating deeply and preventing water infiltrations.

LESION STUCCO is easy to apply with no dripping or detachment. It adheres perfectly to the treated surface, ensuring an excellent anchorage to the paints.

APPLICATION

New Walls:

-The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time.

- Brush the surface, in order to remove any loose leaf flakes and ensure that any rust traces is cleaned up. Remove any old, loose or flaking paint.

- Proceed applying LESION STUCCO ready to use, with a stainless steel spalter.


PLEASE NOTE: As LESION STUCCO is a not sanding product, it presents a transparency problem, therefore before painting it is necessary to fill it with any type of putty in paste or powder

Old Walls:

-The surface to be treated must be dry.

-Scrape off any loose flaking and poorly adhering coating, scraping and washing the surface with plenty of water or using a pressure washer.

-Proceed following the instruction of 'NEW WALL' from the third point onwards.

TECHNICAL DATA	
Nature of the bond	Vinyl copolymer in aqueous emulsion and various additives
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	secondo supportom ² /Lt
Specific weight	N/A
Colors	White
Dry aspect	
Wet aspect	white paste with high viscosity
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	0,500LT
CHARACTERISICS	
Characteristics:	Linea stucchi.
Can be applied on:	Walls,Wood.
for:	Interno ed Esterno.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Spalter inox.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR34** safety data sheet.

ITEM SPECIFICATION

Stucco based on elastic compound in paste form, used for internal and external. Applications to be made on already prepared surfaces of stucco on elastic compound in paste form LESION STUCCO cod.LS01, based on vinyl copolymer, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.