

IDROCEMEOPAC

Water-based Primer

DESCRIPTION

IDROCEMEOPAC is a primer paint for the preparation of wooden or wall supports, which must be treated with water-based enamels.

Its formulation based on alkyd resins gives the product excellent covering, uniforming and filling power.

IDROCEMEOPAC is easy to apply, thanks to its good dilatation, moreover, since it is easy to sand, it gives the finishing product a solid anchorage.

APPLICATION

Wooden surfaces:

Sand lightly to remove raised wood fibres.

Check the condition of old varnishes. Remove any not perfectly adhering parts of the wall.

Level out irregularities in the substrate. Fill holes, cracks and defects with PASTA STUCCO.

Sand lightly with sandpaper and clean.

Proceed with roller or brush, applying two coats of IDROCEMEOPAC primer, to be diluted with water in the following percentages: 1st and 2nd coat 10-20%.

Wall surfaces:

Make sure the surface is well dry. In case of plaster, make sure it has a maturation time of at least 28 days.

Remove the peeling or not perfectly adherent parts of old paints. Completely remove layers of old lime or tempera paints.

For internal surfaces, fill any imperfections with STUCCO TRE STELLE or smooth out any irregularities in the substrate with RASAN STUCCO or K-STUKK; for external surfaces, fill any imperfections with ESTERN STUCCO or smooth out any irregularities in the substrate with RIVENDUIT CALCE .

Sand the grouting and remove dust by brushing.


In presence of mould, treat the surface with SCIK BONIFIK .

Proceed with a roller or brush, applying two coats of IDROCEMEOPAC primer, to be diluted with water in the following percentages: 1st and 2nd coat 10-20%.

TECHNICAL DATA

Nature of the bond	Water-based primer, based on alkyd resins
Viscosity	
Drying Time	1 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	8-10m ² /Lt
Specific weight	N/A
Colors	Bianco
Dry aspect	
Wet aspect	Bianco
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 Years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	0,500LT,5LT,14LT

CHARACTERISTICS

Characteristics:	Sintetico,High Opacity,Uniformante,Riempitivo.
Can be applied on:	Walls,Wood.
for:	Interiors/Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	attPennello,attSpruzzo.
Related products:	.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.