

**SCHEDA TECNICA N°88**

## PRIMER CONSOLIDANTE

Solvent-based consolidating primer

### DESCRIPTION

PRIMER CONSOLIDANTE is an insulating, solvent-based, water-repellent primer able to consolidate particularly chalking wall surfaces already painted with various layers of old paints.

The product improves the cohesion and evens out the absorption of the substrate, creating the ideal anchorage for subsequent layers of paint, which are isolated from the alkaline environment of cementitious and analogous substrates.

### APPLICATION

#### Wall surfaces, plaster, drywall:

The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.

Remove any old paint or peeling parts that do not adhere perfectly to the wall.

For internal surfaces, fill any imperfections with STUCCO 3 STELLE (read TDS n° 33) or smooth out any irregularities in the substrate with RASAN STUCCO (read TDS n° 48) or K-STUKK (read TDS n° 48a); for external surfaces, fill any imperfections with ESTERN STUCCO (read TDS n° 76) or smooth out any irregularities in the substrate with RIVENDUIT CALCE (read TDS n° 48b).

Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.

Make sure the substrate is dry and proceed with a brush, roller or spray gun, applying a coat of PRIMER CONSOLIDANTE, ready to use.

N.B. During the application of the product, we suggest to protect the floor and to make sure that the product has completely evaporated before moving in the room again.



#### COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

[www.rivedil.com](http://www.rivedil.com) - [export@rivedil.com](mailto:export@rivedil.com)

**TECHNICAL DATA**

Nature of the bond	Solvent copolymer
Viscosity	
Drying Time	2 h at touch, 6-8 h complete.
Thinning	Ready to use
Yield	4-5m <sup>2</sup> /Lt
Specific weight	N/A
Colors	Transparent
Dry aspect	Transparent
Wet aspect	Transparent
Storing	Max Temp. +30°C, Min T. +5°C
Stability	years (in sealed, unopened original packing)
VOC	µGr/m <sup>3</sup>
TVOC	N/A
PH	N/A
Cleaning	Water ragia
Packing	20LT,5LT,1LT

**CHARACTERISTICS**

Characteristics:	Linea speciale.
Can be applied on:	Walls,Wood.
for:	Interno ed Esterno.
Certifications:	

**TOOLS AND RELATED PRODUCTS**

Tools:	Brush,Sprayer.
Related products:	RASAN STUCCO,K-STUCC,RIVENDUIT CALCE,STUCCO TRE STELLE,ESTERN STUCCO,SCIK PURAL ACRIL,FISSATIVO TRE STELLE.

**SAFETY INSTRUCTIONS**

Flammable; keep out of reach of flames and sparks; do not smoke; harmful; avoid contact with skin and eyes; do not inhale gases, fumes, vapours, aerosols; if swallowed do not induce vomiting; seek medical advice immediately and show this package or label; keep out of the reach of children; toxic to the environment; do not empty into drains or into water. See SSR79 Safety Data Sheet for further information.

**SPECIFICATION ITEM**

Solvent-based water-repellent insulation for indoor and outdoor use.

Application, on already prepared surfaces, of PRIMER CONSOLIDANTE solvent-based insulation code PRC01, suitable to consolidate and insulate wall supports in the quantities determined by the absorption of the support.

**NOTES**

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com