

**SCHEMA TECNICA N°89**

ANTISALMASTRO S

Solvent based antidusting product

DESCRIPTION

ANTISALMASTRO S is a solvent-based product, designed and tested to block the effect of brackish water on walls for as long as possible.

The raw materials used and their reaction to the pulverization caused by the brackish, contributes, in an evident way, to protect the painting work over time and to keep the treated wall clean.

ANTISALMASTRO S does not eliminate the formation of new salty dust at the root, but it stops it from forming, giving the treated wall a pleasantly clean look.

APPLICATION

Make sure that the support is dry.

In the case of plaster, wait at least 28 days before applying the product.

Remove any old paints or peeling parts that are not perfectly adhering.

For internal surfaces, fill any imperfections with STUCCO 3 STELLE; for external surfaces, fill any imperfections with ESTERN STUCCO .

Sand the fillers and remove dust by brushing.

Make sure the substrate is dry and proceed with a brush or roller to apply one coat of ANTISALMASTRO S, to be diluted with synthetic thinner in the following percentages: about 5-10%.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	N/A
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Diluyente sintetico 5-10%
Yield	4-5m ² /Lt
Specific weight	1,459Kg/Lt
Colors	Transparent
Dry aspect	Transparent
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water ragia
Packing	2,5LT,0,750LT

CHARACTERISTICS	
Characteristics:	Linea speciale.
Can be applied on:	.
for:	Interno ed Esterno.
Certifications:	

TOOLS AND RELATED PRODUCTS	
Tools:	Roller,Brush.
Related products:	STUCCO TRE STELLE,ESTERN STUCCO.

SAFETY INSTRUCTIONS

Flammable; keep out of reach of flames and sparks; do not smoke; harmful; avoid contact with skin and eyes; do not inhale gases, fumes, vapours, aerosols; if swallowed do not induce vomiting; seek medical advice immediately and show this container or label; keep out of the reach of children; toxic to the environment; do not empty into drains or into water. For further information see SSR42a Safety Data Sheet.

SPECIFICATION ITEM

Solvent dust-proofing product. Application of ANTISALMASTRO S cod.ASS01 solvent-based anti-dusting product on already prepared surfaces, suitable to consolidate wall supports in the quantities determined by the absorption of the support. Cost of the supply and installation of the material per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com