

**SCHEDA TECNICA N°117****SCIK PURAL ACRIL AL TITANIO**

Matt, pigmented, acrylic insulation, for internal and external use

DESCRIPTION

SCIK PURAL ACRIL AL TITANIO is an acrylic insulation characterized by an excellent filling and penetrating power, which can also consolidate the wall supports in presence of crumbling surfaces, patches or flaws.

The main purpose of this product is to improve the cohesion and standardize the support absorption, in order to create the ideal anchorage for the next layers of paint, isolating these from the alkaline environment.

APPLICATION

Wall, gypsum, plasterboard:

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time.
- Remove any layers of old paint or imperfectly anchored parts and sand the entire surface.
- Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.
- Make sure the surface is dry and proceed applying with brush or roller 1 coat of SCIK PURAL ACRIL AL TITANIO, ready to use.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273


P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Acrylic copolymer in water dispersion
Viscosity	
Drying Time	1 h at touch, 3-6 h complete.
Thinning	Ready to use
Yield	secondo diluizione e supportom ² /Lt
Specific weight	1,5Kg/Lt
Colors	White
Dry aspect	White-pigmented
Wet aspect	Milky
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	5LT,10LT,15LT

CHARACTERISTICS

Characteristics:	Linea Isolanti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR118** safety data sheet.

ITEM SPECIFICATION

Fixative based on acrylic resins. Applications to be made on already prepared surfaces of acrylic water-based wall fixative SCIK PURAL ACRIL cod.SPA01, in a single layer, in quantities determined by the support absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com