

SCHEDA TECNICA N°136

SCIK FONDO UNIFORMANTE

Fibrous acrylic self-leveling coating base.

DESCRIPTION

SCIK FONDO UNIFORMANTE is a fibrous acrylic self-leveling coating base.

This special product has been designed for wall preparation in the event of plaster, granules from plaster and also for faulty surfaces not painted for years.

APPLICATION

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time.
- Proceed applying with roller or brush, a coat of SCI K FONDO UNIFORMANTE ready to use or diluted with water as necessary (max. 5-10%).
- Allow to dry from 12 to 24 hours, depending on temperature, before proceeding with the final coat of paint.

TECHNICAL DATA

Nature of the bond

Special additives in aqueous emulsion

Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Water 10-15%
Yield	4-5m ² /Lt
Specific weight	N/A
Colors	White
Dry aspect	White cream
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	15LT,5LT

CHARACTERISTICS

Characteristics:	Linea Restauri.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Spalter.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates.
Use the product in accordance with the relevant health and safety regulations of the country.

Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste.
For further information please refer to **SSR8** safety data sheet.

ITEM SPECIFICATION

Special, self- leveling paint washable, sanitizing for exteriors and interiors.

Applications to be made on the already prepared surfaces of SCIK FONDO UNIFORMANTE based on copolymers in aqueous dispersion and mineral fillers, in a single layer, in quantities determined by the support absorption.

Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.