

**SCHEDA TECNICA N°137**

SCIK FONDO COPRENTE

Special paint designed as a base for bright colors and strong tones made with neutral bases

DESCRIPTION

SCIK FONDO COPRENTE is a quartz acrylic paint with excellent filling and smoothing power, suitable for the treatment of internal and external supports.

Its formulation based on special additives, is designed as a base for bright colors and strong tones made with neutral bases.

SCIK FONDO COPRENTE is also recommended as wall supports preparation base, in presence of stucco, patches or flaws.

APPLICATION -The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time. - Proceed applying with roller or brush, a coat of SCIK FONDO COPRENTE ready to use or diluted with water as necessary (max. 5-10%). - Allow to dry from 24 to 36 hours, depending on temperature, before proceeding with color painting.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Special additives in water emulsion
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Water 15-20%
Yield	5-6m ² /Lt
Specific weight	1,600Kg/Lt
Colors	Straw
Dry aspect	Matt
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	13LT,5LT

CHARACTERISTICS

Characteristics:	Linea Rivestimenti.
Can be applied on:	Walls,Wood.
for:	Esterno.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR8** safety data sheet.

ITEM SPECIFICATION

Special primer, washable, sanitizing for exteriors and interiors. Applications to be made on already prepared surfaces of SCIK FONDO COPRENTE paint, based on copolymers in aqueous dispersion and mineral fillers, in a single layer, determined in quantities by the support absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com