

SCIK BONIFIK

DESCRIPTION

SCIK BONIFIK is a specific agent used for the cleaning of internal and external surfaces, before being treated.


The product is recommended for any type of wall support infected by molds, fungi and algae and it is also designed for reclaiming the substrate and bringing it back to its original appearance.

SCIK BONIFIK can also be applied on pre-painted walls and existing plastic coatings.

APPLICATION

APPLICATION

- Proceed applying SCIK BONIFIK by brush or spray directly onto the substrate. Be sure to wear a visor mask especially when applied by spray.
- Brush the surface after 12-24 hours.
- Repeat several times the treatment, in case of a consistent fungi and molds presence, until the surfaces are completely restored.
- Paint the substrate with LINEA SCIK line.

TECHNICAL DATA	
Nature of the bond	N/A
Viscosity	
Drying Time	2 h at touch, 24-48 h complete.
Thinning	Water 1:1
Yield	15-20m ² /Lt
Specific weight	1Kg/Lt
Colors	
Dry aspect	
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	0,750LT,5LT
CHARACTERISICS	
Characteristics:	Linea Isolanti.
Can be applied on:	Walls,Wood.
for:	Interno ed Esterno.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Brush,Sprayer.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR146** safety data sheet.

ITEM SPECIFICATION

Specific agent used for the cleaning of internal and external surfaces infected by molds and fungi. Applications to be made on already prepared surfaces of SCIK BONIFIK cod.SK01 special agent, based on oxidizing additives, suitable for cleaning infected walls, at least into 2 layers, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.