

**SCHEDA TECNICA N°183** 

## **PLASTUK**

Plaster to fill cracks and holes

## **DESCRIPTION**

PLASTUK è uno speciale stucco leggero per lesioni > 0.5 cm.

Non ritira e non spacca e si applica con la spatola per lo stucco.

PLASTUK is a special light plaster (filler) for cracks and holes > 0.5 cm.

It does not shrink and does not split and the product can be applied with the putty spatula.

## **APPLICATION**

Ready to use product. For indoor and outdoor use. If necessary dilute it with water up to a maximum of 10-15%. After the application and complete drying, if necessary of PLASTUK can be sanded.



| TECHNICAL DATA             |  |
|----------------------------|--|
| Nature of the bond         | N/A  |
| Viscosity                  |  |
| Drying Time                | h complete.                                  |
| Thinning                   |  |
| Yield                      | m²/Lt  |
| Specific weight            | N/A  |
| Colors                     |  |
| Dry aspect                 |  |
| Wet aspect                 |  |
| Storing                    | Max Temp. °C                                 |
| Stability                  | years (in sealed, unopened original packing) |
| voc                        | μGr/m³                                       |
| TVOC                       | N/A  |
| РН                         | N/A  |
| Cleaning                   |  |
| Packing                    |  |
| CHARACTERISICS             |  |
| Characterisics:            |  |
| Can be applied on:         |  |
| for:                       |  |
| Certifications:            |  |
| TOOLS AND RELATED PRODUCTS |  |
| Tools:                     |  |
| Related products:          |  |

## **NOTES**

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.

