

**SCHEDA TECNICA N°35****RIV K.B.**

Adhesive resin for mortars and grouts

DESCRIPTION

RIV K.B. is a resin used to improve the adhesion of mortars on various substrates.

Once mixed with mortar, the product acquires excellent adhesive power, better resistance to chemicals and to the freeze-thaw cycle, a reduced concrete permeability to solvent oils and higher elasticity.

APPLICATION**Preparation process:**

- Mix RIV. K.B. with water before the aggregates amalgamation.

For grout:

- Lt 1 of RIV K.B (already mixed with water) + Kg 3 of cement + Lt 1 of water.

For mortar thickness:

- Lt 4 of RIV K.B (already mixed with water) + Kg 100 of finished mortar.

Mix carefully in order to obtain a homogeneous lump-free paste.

TECHNICAL DATA

Nature of the bond	Acrylic copolymer in water dispersion
Viscosity	
Drying Time	2 h complete.
Thinning	Ready to use
Yield	m ² /Lt
Specific weight	N/A
Colors	
Dry aspect	liquid
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	5LT,0,750LT

CHARACTERISTICS

Characteristics:	Linea restauro.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR69** safety data sheet.

ITEM SPECIFICATION:

Adhesive resin for mortars and grouts. Applications to be made on the already prepared surfaces of liquid, adhesive resin RIV. K.B. cod. RKB01, based on selected aggregates and specific additives, at least 2 layers, in the quantities determined by the substrate absorption. Supply and installation of the material €..... per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

PIVA 01122590753

www.rivedil.com - export@rivedil.com