

**SCHEDA TECNICA N°59**

BITUMINIO

Solvent-based aluminium protective paint for sheat

DESCRIPTION

BITUMINIO is a special aluminium paint which, thanks to its formulation, guarantees perfect protection and refraction to UV rays.

The product can be applied on various types of support such as bituminous coverings, pipes, metal tanks, but it has been studied mainly for the protection of sheaths.

APPLICATION

Metal surfaces:

Make sure that the substrate is dry and free of grease, oil or dust.

Proceed with a brush or roller, applying a coat of BITUMINIO, ready to use.

Surfaces in bituminous sheath:

Make sure that 40-50 days have elapsed from the laying of the sheath.
Proceed with brush or roller, applying one coat of BITUMINIO, ready to use.

TECHNICAL DATA	
Nature of the bond	Selected oxidizing bitumen and metallic aluminium
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	6-8m ² /Lt
Specific weight	N/A
Colors	Aluminium grey
Dry aspect	
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water ragia
Packing	18LT,5LT

CHARACTERISTICS	
Characteristics:	Linea speciale.
Can be applied on:	.
for:	Esterno.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Roller,Brush.
Related products:	.

SAFETY INSTRUCTIONS

Flammable; keep out of reach of flames and sparks; do not smoke; harmful; avoid contact with skin and eyes; do not inhale gases, fumes, vapours, aerosols; if swallowed do not induce vomiting; seek medical advice immediately and show this package or label; keep out of the reach of children; toxic to the environment; do not empty into drains or into water. See SSR59 Safety Data Sheet for further information.

SPECIFICATION ITEM

Solvent-based aluminium protective paint for sheaths.

Applications, on already prepared surfaces, of BITUMINIO aluminium paint code BM02 based on aluminium, in a single layer, in the quantities determined by the absorption of the support.

NOTES

- Cost of Supply and installation of the material per sqm.....
- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
 - In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
 - Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO
 Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy
 Tel. (+39) 0832 731293 - (+39) 0832 731273
 P.IVA 01122590753
 www.rivedil.com - export@rivedil.com