

**SCHEDA TECNICA N°65****SINT PISTA TRASPARENTE**

Synthetic paint, solvent based

**DESCRIPTION**

SINT PISTA TRASPARENTE is a product based on solvent acrylic resins, designed and formulated for the protection of internal and external supports, particularly subject to the erosive action of water or atmospheric agents.

The product has excellent water-repellent and washable properties, as it prevents water from penetrating the substrate, it does not retain dirt and dries quickly.

SINT PISTA TRASPARENTE, in addition to protecting the support, revives its colour, giving it a glossy appearance.

SINT PISTA TRASPARENTE can be applied on various types of exposed surfaces, such as cement, terracotta, carparo, Lecce stone, slabs, etc..

**APPLICATION**

- Remove, by brushing or washing, surface scabs and dirt.  
In the presence of mould, treat the surface with SCIK BONIFIK (see technical data sheet n°146).  
Make sure the substrate is well dry and proceed with brush, roller or spray, applying 1 coat of SINT PISTA TRASPARENTE ready to use or to dilute, as needed, with nitro thinner.  
Apply a 2nd coat after 4 h.

N.B. During the application of the product, we suggest to protect the floors and to make sure that the product evaporates completely before entering the room.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

**TECHNICAL DATA**

|                    |                                                |
|--------------------|------------------------------------------------|
| Nature of the bond | Special resins                                 |
| Viscosity          |                                                |
| Drying Time        | 2 h at touch, 12-24 h complete.                |
| Thinning           | Diluyente sintetico 20-25%                     |
| Yield              | 4-5m <sup>2</sup> /Lt                          |
| Specific weight    | N/A                                            |
| Colors             | Transparent, Cement Grey, Brick Red and Green. |
| Dry aspect         | Glossy                                         |
| Wet aspect         |                                                |
| Storing            | Max Temp. +30°C, Min T. +5°C                   |
| Stability          | 2 years (in sealed, unopened original packing) |
| VOC                | µGr/m <sup>3</sup>                             |
| TVOC               | N/A                                            |
| PH                 | N/A                                            |
| Cleaning           | Diluyente nitro                                |
| Packing            | 20LT,5LT                                       |

**CHARACTERISTICS**

|                    |                     |
|--------------------|---------------------|
| Characteristics:   | Linea speciale.     |
| Can be applied on: | .                   |
| for:               | Interno ed Esterno. |
| Certifications:    |                     |

**TOOLS AND RELATED PRODUCTS**

|                   |               |
|-------------------|---------------|
| Tools:            | Roller,Brush. |
| Related products: | SCIK BONIFIK. |

**SAFETY INSTRUCTIONS**

Flammable; keep out of reach of flames and sparks; do not smoke; harmful; avoid contact with skin and eyes; do not inhale gases, fumes, vapours, aerosols; if swallowed do not induce vomiting; seek medical advice immediately and show this package or label; keep out of the reach of children; toxic to the environment; do not empty into drains or into water. See SSR64 Safety Data Sheet for further information.

**SPECIFICATION ITEM**

Solvent-based synthetic paint for concrete floors .

Application, on already prepared surfaces, of synthetic solvent based paint SINT PISTA TRASPARENTE cod.SP01 in at least 2 layers, with a consumption determined according to the absorption of the substrate.

**NOTES**

Cost of the Supply and installation of the material in sq.m. ....

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.

- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.

- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com