

**SCHEDA TECNICA N°66**

MURAL 1

Wall protection product, solvent-based, acrylic consolidating water-repellent

DESCRIPTION

MURAL 1 is a wall protection product composed of solvent-based acrylic resins, designed as a barrier for internal and external support, particularly subject to the erosive action of water or exposed to atmospheric agents.

The product has excellent water-repellent and washable properties, in fact it prevents water from penetrating into the substrate.

In addition, besides protecting the support, MURAL1 brightens the colour giving it a glossy appearance.

MURAL 1 can be applied on different types of visible surfaces, such as cement, terracotta, carparo, pietra leccese (Lecce stone), slabs, etc.

APPLICATION

Cement, terracotta, carparo, pietra leccese (Lecce stone), slabs surfaces:

- Brush the surface, in order to remove any loose leaf flakes and ensure that surface crusts and traces of dirt are cleaned up.
- In the presence of molds, treat the surface with SIKK BONIFIK.
- Make sure the surface is dry and with a brush, roller or spray proceed applying 1 coat of MURAL 1 ready to use or dilute, if necessary, with alcohol or synthetic diluent.

PLEASE NOTE: We advise to protect the floors and to ensure the complete evaporation of the product before staying in the treated environment.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Siloxanic copolymers and synthetic solvent-based acrylic resins
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	8-10m ² /Lt
Specific weight	0,827Kg/Lt
Colors	transparent glossy
Dry aspect	Transparen glossy
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water ragia@diluyente sintetico
Packing	20LT,5LT,1LT

CHARACTERISTICS

Characteristics:	Linea idrorepellenti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush,Sprayer.
Related products:	SCIK BONIFIK.

SAFETY INSTRUCTIONS:

Flammable product:

- Keep away from heat, sparks and open flames – No smoking.
- Avoid contact with skin and eyes.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

If swallowed, do NOT induce vomiting: immediately consult the doctor showing the product label or the container.

Keep out of reach of children. Avoid release to the environment, as toxic. Do not empty into drains or the aquatic environment. For further information, please consult the SSR66 safety data sheet.

ITEM SPECIFICATION:

Water-repellent solvent-based consolidating acrylic protective agent for internal and external surfaces. Applications made on already prepared surfaces of water-repellent solvent-based MURAL 1 cod.M101 based on siloxanic copolymers and acrylic resins in water dispersion, in a single layer, in quantities determined by the substrate absorption. Supply and installation of material € **NOTES**... per sqm.

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com