

**SCHEDA TECNICA N°69**

MURAL 4

Wall protection solvent-based, silicone, water repellent

DESCRIPTION

MURAL 4 is a wall protection product composed of solvent based on non-filmogenic silicone resins, designed as a barrier for internal support, particularly the external one subject to the erosive action of water or exposed to atmospheric agents.

MURAL 4 creates a water-repellent barrier, penetrating deeply into the substrate and leaving the water vapor permeability unchanged. Therefore the walls will always be perfectly dry: no water penetrates inside and water vapor comes out.

In addition, besides protecting the support, MURAL 4 does not affect the color and the aspect.

MURAL 4 can be applied on different types of visible surfaces, such as cement, terracotta, carparo, tufa, pietra leccese (Lecce stone), slabs, etc.

APPLICATION

Cement, terracotta, carparo, tufa, pietra leccese (Lecce stone), slabs surfaces:

Brush the surface, in order to remove any loose leaf flakes and ensure that surface crusts and traces of dirt are cleaned up.

- In the presence of molds, treat the surface with SCIK BONIFIK.
- Make sure the surface is dry and with a brush, roller or spray proceed applying 1 or 2 coats of MURAL 4 ready to use.

PLEASE NOTE: We advise to protect the floors and to ensure a good ventilation before staying in the treated environment.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Non-filmogenic, silicone resins
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	4-5m ² /Lt
Specific weight	N/A
Colors	transparent
Dry aspect	transparent
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water ragia@diluyente sintetico
Packing	20LT,5LT,1LT

CHARACTERISTICS

Characteristics:	Linea idrorepellenti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush,Sprayer.
Related products:	SCIK BONIFIK.

SAFETY INSTRUCTIONS:

Flammable product:

- Keep away from heat, sparks and open flames – No smoking.
- Avoid contact with skin and eyes.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

If swallowed, do NOT induce vomiting: immediately consult the doctor showing the product label or the container.

Keep out of reach of children. Avoid release to the environment, as toxic. Do not empty into drains or the aquatic environment. For further information, please consult the SSR69 safety data sheet.

ITEM SPECIFICATION:

Protective, solvent-based, silicone, water repellent for internal and external surfaces. Applications made on already prepared surfaces of solvent-based, silicone, water repellen MURAL 4 cod.M401 based on non-filmogenic, silicone resins, in one or two layers layer, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com