

SCHEDA TECNICA N°113

LUCIDO G.M.

Fast drying acrylic solvent-based polishing paint for granite-marble

DESCRIPTION

LUCIDO G.M is a solvent- based acrylic resins product, designed for the protection of internal and external support subject to the erosive action of water or exposed to atmospheric agent, but specifically formulated for the treatment of granite-marble.

The product has excellent water-repellent and washable properties, infact it prevents water from penetrating into the substrate.

Due to its quick drying quality this polish is fast and simple to apply.

In addition, besides protecting the support, LUCIDO G.M brightens the colour giving it a glossy appearance.

APPLICATION

Granite-marble surfaces:

- Brush the surface, in order to remove any loose leaf flakes and ensure that surface crusts and traces of dirt are cleaned up.

- Make sure the surface is dry and with a brush or roller proceed applying 1 or 2 coats of LUCIDO G.M. ready to use or to be diluted with DILUENTE NITRO as necessary.



COLORIFICIO RIVEDIL di COSIMO CODARDO Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy Tel. (+39) 0832 731293 - (+39) 0832 731273 P.IVA 01122590753 www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	Synthetic acrylic resins with solvent
Viscosity	
Drying Time	h complete.
Thinning	Ready to use
Yield	0,500-0,700m²/Lt
Specific weight	N/A
Colors	Transparent glossy
Dry aspect	Transparen glossy
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
voc	μGr/m³
тиос	N/A
РН	N/A
Cleaning	Diluente nitro
Packing	20LT,5LT
CHARACTERISTICS	
Characteristics:	Linea idrorepellenti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Roller,Brush.
Related products:	DILUENTE NITRO.

SAFETY INSTRUCTIONS:

Flammable product:

- Keep away from heat, sparks and open flames No smoking.
- · Avoid contact with skin and eyes.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

If swallowed, do NOT induce vomiting: immediately consult the doctor showing the product label or the container. Keep out of reach of children. Avoid release to the environment, as toxic. Do not empty into drains or the aquatic environment. For further information, please consult the SSR113 safety data sheet.

ITEM SPECIFICATION:

Protective, acrylic, quick drying, solvent-based polish, for internal and external surfaces. Applications to be made on the already prepared surfaces of acrylic, solvent-based polish LUCIDO G.M. cod.LGM01 based on acrylic resins in aqueous solution, in one or two layers, in quantities determined by the substrate absorption. Supply and installation of material € per sqm. **NOTES**

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.

- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.

- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy Tel. (+39) 0832 731293 - (+39) 0832 731273 P.IVA 01122590753 www.rivedil.com - export@rivedil.com