

GRANIGLIATO E CERAMIZZATO

Plastic coating in multicolored marble granules

DESCRIPTION

GRANIGLIATO - CERAMIZZATO is a plastic coating with a multicolor granigliato-ceramizzato effect, for both interiors and exteriors.

The product is mainly composed of homogeneous multicolored marble granules in precious acrylic resins emulsion and various additives.

The high quality resins used, after polymerization, give the coating an excellent resistance to scratches and shocks, but also an evident brightness, leaving the natural color of the quartz unchanged.

APPLICATION

New Walls:

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time.
- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster.
- Level out imperfections of the internal support with RASAN STUCCO or with K-STUKK; use instead RIVENDUIT CALCE for the external support. In case of holes or micro-cracks, fill the inner walls with STUCCO TRE STELLE and the external ones with ESTERN STUCCO.
- Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.
- Apply 1 coat of SCIK PURAL ACRIL insulation or FISSATIVO ACRILICO TRE STELLE.
- Apply the special SOTTOFONDO PER RIVESTIMENTI.
- Proceed applying with spatula, a coat of GRANIGLIATO - CERAMIZZATO ready to use.

Old Walls

- The surface to be treated must be dry.
- Scrape off any loose flaking and poorly adhering coating.
- Proceed following the instruction of 'NEW WALL' from the third point onwards.

TECHNICAL DATA

Nature of the bond	acrylic copolymer in aqueous emulsion and quartz granules
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	grana media@4,000-4,500@grana fine@3,500-4,000m ² /Kg
Specific weight	N/A
Colors	see chart: GRANIGLIATO - CERAMIZZATO
Dry aspect	multicolor
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	25KG

CHARACTERISICS

Characteristics:	Linea Rivestimenti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Spalter inox.
Related products:	RASAN STUCCO,K-STUCC,RIVENDUIT CALCE,STUCCO TRE STELLE,ESTERN STUCCO,SCIK PURAL ACRIL,FISSATIVO TRE STELLE,SOTTOFONDO PER RIVESTIMENTI.

SAFETY INSTRUCTIONS

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste.

ITEM SPECIFICATION:

Plastic coating in multicolored marble granules for interiors and exteriors.

Applications to be made on already prepared surfaces of plastic coating GRANIGLIATO cod.GRN01, in quantities determined by the substrate absorption.

Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.