RIVEDIL®
EXCLUSIVE PAINT
MADE IN ITALY
By C.C

SCHEDA TECNICA N°127

VERNICOLOR
Impregnating paint, colored, with a glossy effect

DESCRIPTION

VERNICOLOR is special impregnating paint, colored, with a glossy effect, designed for all wooden supports.

The product formulation based on modified alkyd resins, offers an excellent penetrating power, used as protection against atmospheric agents.

VERNICOLOR enables not only coloured and glossy but also fillers and water repellents finishes to be obtained since it forms a microporous film which easily permits the passage of water vapour.

Furthermore it acts both as an impregnating agent and as a decorative finish and it is characterized by extreme ease and speed of application.

APPLICATION

NEW WOOD SURFACES:

- Sand to remove any raised wood flakes.
- The substrate has to be well prepared and suitable for coating, so make sure the wood is not damp.
- Level out imperfections with PASTA STUCCO.
- Sand the grouting and then eliminate dust deposits.
- After 6-12 hours, proceed applying with brush or spray, 2 coats of VERNICOLOR, which has to be thinned up with ACQUA RAGIA (white spirit), in the following percentages: approx 5 -10%.

Pre-PAINTED WOOD SURFACES:

- Verify the condition of the old paint. Scrape off any loose flaking and poorly adhering coating.
- Proceed as for the new wood surfaces from second point onwards

colorificio Rivedil
made in Italy

COLORIFICIO RIVEDIL di COSIMO CODARDO
Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy
Tel. (+39) 0832 731293 - (+39) 0832 731273
P.IVA 01122590753
www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Modified alkyd resins
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Water ragia 5-10%
Yield	8-10m²/Lt
Specific weight	0,900Kg/Lt
Colors	Vernicolor chart
Dry aspect	Bright- colored
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	years (in sealed, unopened original packing)
VOC	µGr/m³
TVOC	N/A
PH	N/A
Cleaning	Water Ragia
Packing	2,5LT,0,750LT

CHARACTERISTICS

Characteristics:	Linea Legno.
Can be applied on:	Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Brush,Sprayer.
Related products:	PASTA STUCCO,ACQUA RAGIA.

SAFETY INSTRUCTIONS:
Harmful and flammable product:

- Keep away from heat, sparks and open flames – No smoking.
- Avoid contact with skin and eyes.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

If swallowed, do NOT induce vomiting: immediately consult the doctor showing the product label or the container.
Keep out of reach of children. Avoid release to the environment, as toxic. Do not empty into drains or the aquatic environment. For further information, please consult the SSR127 safety data sheet.

ITEM SPECIFICATION:
Impregnating paint, colored, designed for all wooden supports. Applications to be made on already prepared surfaces of impregnating paint, with a glossy effect for wood VERNICOLOR cod. VRC01 based on modified alkyd resins, in 2 layers at least, in quantities determined by the substrate absorption. Supply and installation of material € .... per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.