

SCHEDA TECNICA N°203

FILO D'ORIENTE

Decorative Wild Oriental Silk effect

DESCRIPTION

FILO D'ORIENTE is the new revolutionary decorative effect of the DELUXE COLLECTION range, which reproduces on the walls the effect of Wild Oriental Silk with delicate gold or silver effects.

Ideal for any type of environment and also recommended for trendy premises, homes or ethnic environments.

The system is composed of two bases:

- FILO D'ORIENTE SILVER
- FILO D'ORIENTE GOLD

The product can be used exclusively on internal supports, after an appropriate treatment with our special primer DECOR FONDO.

APPLICATION

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster. In case of old walls make sure there is no poor or dusty paint: remove them if necessary as well as flaking paint.
- Apply 1 coat of SCIK PURAL ACRIL primer insulation if necessary.
- Apply with a brush or roller, one or two coats of DECOR FONDO PRIMER which has to be thinned up to 5-10 % with water. Allow to dry perfectly (from 6 to 12 hours).

EFFETTO FILO DI SETA (SILK WIRE EFFECT):

- Apply FILO D'ORIENTE -ready to use or colored with the SUPERTINTING system- uniformly, with a short-haired roller.
- Straight after the application by roller, with fresh product, brush horizontally the entire surface using the SPALTER.
- Allow to dry perfectly.
- Apply the 2nd coat of FILO D'ORIENTE always using a short haired roller and immediately after application, since the product is still fresh, stroke it in vertical direction, using the special RIGATO tool (ridging tool).
- Allow to dry.

EFFETTO SETA A PENNELLO (BRUSH SILK EFFECT)

- After checking the color chart, add to the base you choose, the quantity of dye necessary to obtain the desired colour.
- Mix carefully until the base is uniformly colored.
- Apply a coat of FILO D'ORIENTE with a brush (Spalter 100) spreading the product along different directions, until the entire surface to be decorated is covered.
- Subsequently on still applied fresh product, with empty brush, gently stroke in order to remove any accumulation of product.
- Proceed adopting this technique over the entire surface.

- After about 10-20 min, gently stroke again the surface by using the SPATULA TD in order to obtain light and shadow effects.

EFFETTO BICOLORE (TWO - TONE EFFECT):

- After checking the color chart, add to the base you choose, the quantity of dye necessary to obtain the desired colour.
- Mix carefully until the base is uniformly colored.
- Apply a coat of FILO D'ORIENTE with a roller, spreading the product along different directions, until the entire surface to be decorated is covered.
- After about 10-20 min, gently stroke again the surface by using the SPALTER with no product, and smooth the decorated surface by brushing in one direction.
- After about 10-20 min, just choose a second colour base and repeat the first three points of the process listed above.
- Smooth the surface just decorated with the ATTREZZO RIGATO (ridging tool) following a perpendicular stretch to the previous one.

TECHNICAL DATA	
Nature of the bond	Vinyl
Viscosity	
Drying Time	2 h at touch, 24 h complete.
Thinning	Ready to use
Yield	2-3m²/Lt
Specific weight	1,162Kg/Lt
Colors	Silver, Gold
Dry aspect	Wild Oriental Silk with delicate gold or silver effects
Wet aspect	Liquid -mellow
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
voc	150μGr/m³
TVOC	490μGr/m³
PH	7-8°C
Cleaning	Water and Soap
Packing	0.750LT,5LT
CHARACTERISICS	
Characterisics:	Breathable, Environmentally friendly.
Can be applied on:	Walls,Wood.
for:	Interiors.
Certifications:	Con size
TOOLS AND RELATED PRODUCTS	
Tools:	Roller, Spalter 100, Ridging Toole.
Related products:	DECOR FONDO (WHITE).

The raw materials used are natural and may have small differences depending on the batchs used. Therefore it is recommended to use the same batch of product for the same work to be carried out. Where this is not possible just mix the batches together.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.