

SCHEDA TECNICA N°212

TERRE D'ITALIA EVOLUTION

Decorative finish made of large size flakes

DESCRIPTION

TERRE D'ITALIA EVOLUTION is a new decorative effect based on large size flakes. It results in modern and stylish finishes, following an easy and fast application.

The product, which contains white flocculi, is characterized by an extreme ease of application and is suitable for any kind of environment or style for its simplicity and delicacy.

APPLICATION

- Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.
- Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules, on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc.
- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- See the TERRE D'ITALIA EVOLUTION color chart and choose the colour you want.
- Proceed with the dilution or coloration of DECOR FONDO considering that:
- EVOLUTION 1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 17, 18, 19, 20, 21, 22, 23, 24 have a WHITE base (DECOR FONDO should be only diluted and not colored) and flocs ready to use, depending on the chosen color;
- EVOLUTION 10, 12, 13, 14, 15, 16, 25, 26, 27, 28, 29, 30, 31, 32 have a COLORED base (DECOR FONDO should be diluted and colored with the new "SUPERTINTING" system) and flocs ready to use, depending on the chosen color;
 - EVOLUTION 33, 34, 35, 36, 37, 38, 39 have a METAL base and both the base and the flocs are ready to use.
- Apply with a brush or roller one or two coats of DECOR FONDO PRIMER (diluted with 5-10 % water).
- Apply the ready to use or previously colored TERRE D'ITALIA EVOLUTION using the SPALTER special tool. We recommend using an average amount of product and spreading the product with it's flocculi in a criss cross pattern.
- After about 20 minutes, deglaze with the decorative tool SPATULA TD or with the STANLESS STEEL TROWEL.
- Allow to dry to appreciate the final effect.

OUTDOOR APPLICATION:

- Apply the TERRE D'ITALIA EVOLUTION by airless or using the SPALTER special tool according to the desired effect.
- Protect the support with the FINITURA F.T.

APPLICATION TO THE GROUND:

- Apply TERRE D'ITALIA EVOLUTION by airless OR using the SPALTER special tool.
- Protect with one of the SCUDO POLIURETANICO (Glossy, Matt, Satin)

TECHNICAL DATA	
Nature of the bond	waterborne fine resine
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	5-6m²/Lt
Specific weight	1,028Kg/Lt
Colors	Neutral
Dry aspect	Ancient and Faded
Wet aspect	Pudding like
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
voc	30μGr/m³
TVOC	130μGr/m³
РН	7-8°C
Cleaning	Water and Soap
Packing	0.750LT,2.5LT
CHARACTERISICS	
Characterisics:	Washable, Environmentally friendly.
Can be applied on:	Walls, Wood.
for:	Interiors/Exteriors.
Certifications:	Towns to the second sec
TOOLS AND RELATED PRODUCTS	
Tools:	Spalter 100, Spalter 70, TD Spalter, Sprayer.
Related products:	DECOR FONDO.

CAUTION:

- N.4 The flocculi in the product are obtained by chemical reaction, for this reason: we can not guarantee the same characteristics from one floculi to another; stability is also limited in time. It is therefore recommended to use the same lot for the same work to be carried out. If this is not possible, manually mix the batches together (do not use an electromechanical tool).

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.