

## **COLORI D'ITALIA**

Decorative wax in fibrous paste form.

### **DESCRIPTION**

COLORI D'ITALIA is a fibrous paste for interiors and exteriors.

This product gives an antique character to rustic interiors or exterior facades.

COLORI D'ITALIA has transpirant and sound-insulating characteristics, and increases thermal efficiency as well.

### **APPLICATION**

- Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.
- Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules , on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc. .
- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Apply with a brush or roller one or two coats of DECOR FONDO PRIMER diluted with 5-10 % water.
- Smooth the entire surface applying COLORI D'ITALIA with a stainless steel trowel copiously, in an irregular, rustic manner.
- Whilst the product is not yet completely dry, shave the surface with the Spatula TD.
- Allow the product a drying time of at least 12-24 hours, according to temperature conditions.
- Apply the colored CERA C.I. with a brush, in rotating strokes.
- After 15-20 minutes, use paper to polish the surface giving the wax an antique effect.

#### **DECORAZIONI RIVEDIL S.r.l.**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

[www.rivedil.com](http://www.rivedil.com) - [export@rivedil.com](mailto:export@rivedil.com)

<b>TECHNICAL DATA</b>	
Nature of the bond	Acrylic resins
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	0,50-0,60m <sup>2</sup> /Lt
Specific weight	1,355Kg/Lt
Colors	Bianco
Dry aspect	Antique
Wet aspect	Pasty
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	10µGr/m <sup>3</sup>
TVOC	40µGr/m <sup>3</sup>
PH	11-12°C
Cleaning	Water and Soap
Packing	4LT,10LT,15LT
<b>CHARACTERISICS</b>	
Characteristics:	Breathable,Soundproofing,Thermal insulant.
Can be applied on:	Walls.
for:	Interiors/Exteriors.
Certifications:	
<b>TOOLS AND RELATED PRODUCTS</b>	
Tools:	attfr,TD Spalter.
Related products:	DECOR FONDO.

#### CAUTION:

- The raw materials used are natural and may have small differences depending on the batches used. Therefore it is recommended to use the same batch of product for the same work to be carried out. Where this is not possible just mix the batches together.

#### NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

#### DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com