

SCHEDA TECNICA N°262

TERRE D'ITALIA PANTHER

Decorative finish made of flakes with 2 colors

DESCRIPTION

TERRE D'ITALIA PANTHER is the decorative created by merging two different colours of flakes that create an original effect particularly suitable for modern environments. This product is available in 6 different bases and is applied with the special SPALTER DUO tool.

APPLICATION

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster. In case of old walls make sure there is no poor or dusty paint: remove them if necessary as well as flaking paint.
- Apply 1 coat of SCIK PURAL ACRIL insulation if necessary.
- Choose from the color chart
- Apply one or two coats of white DECOR FONDO. Use DECOR FONDO thinned at 5-10% with water.
- Allow to dry perfectly (from 12 to 24 hours).
- Proceed applying TERRE D'ITALIA PANTHER using the special SPALTER DUO tool, which is made up of two SPALTER 70 brushes that allow the simultaneous application of two different colors. Please pay attention tonever invert the two brushes with their cans.
- Apply the decoration on the surface in an alternating and uniform way, performing cross movements and mixing the two opalescent colors with different intensity on the whole surface.
- When the product is drying (wait at least 5-10 min), deglaze with the decorative tool SPATULA TD or with the STANLESS STEEL TROWEL.

TECHNICAL DATA	
Nature of the bond	Waterborne fine resine
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	4-6m²/Lt
Specific weight	1Kg/Lt
Colors	Silver, Blue, Gold, Red, Green, Violette
Dry aspect	Decorative finish made of flakes with 2 colors
Wet aspect	Pudding like
Storing	Max Temp. +30°C, Min T. +5°C
Stability	10-12 Months (in sealed, unopened original packing)
voc	10μGr/m³
TVOC	N/A
PH	7-8°C
Cleaning	Water and Soap
Packing	0.750LT,2.5LT
CHARACTERISTICS	
Characteristics:	
Can be applied on:	Walls,Wood.
for:	Interiors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	attsduo, Stainless Steel Trowel 200x80cm.
Related products:	DECOR FONDO DUO.

CAUTION:

- The flocculi in the product are obtained by chemical reaction, for this reason: we can not guarantee the same characteristics from one floculi to another; stability is also limited in time. It is therefore recommended to use the same lot for the same work to be carried out. If this is not possible, manually mix the batches together (do not use an electromechanical tool).

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.