

TDS N°107

TRASPARENTE SPACCANTE

Special primer waterborne for splitting effect

DESCRIPTION

TRASPARENTE SPACCANTE is a paint waterborne that you can apply after the drafting of DECOR FONDO to obtain the version TERRA NOSTRA CRAQUELEE or SP CRAQUELEE.
The product is essential to obtain the splitting effect.

APPLICATION

- Make sure the surface is completely dry. In case of plaster, make sure it has a maturation time of at least 28 days (this time depending on temperature).
- Make sure that the support is well prepared and it is suitable for painting (in other words: dry plaster, removing any granules of plaster. In case of old walls, make sure that there are no poor or floury paintings, and possibly remove etc.
- If necessary, apply one coat of primer SCIK PURAL ACRIL.
- Proceed with application by brush or roller (one or two coats) of DECOR FONDO. It may be diluted with water in the following percentages: 5-10% approximately.
- Shake well before use TRASPARENTE SPACCANTE.
- When dry, proceed with a short pile roller to apply a coat of special paint TRASPARENTE SPACCANTE. Taking care to cover well and evenly over the surface.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	Special acrylic resin and various additives.
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	10-12m ² /Lt
Specific weight	1,076Kg/Lt
Colors	Transparent
Dry aspect	Glossy transparent
Wet aspect	Liquid blue
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 Years (in sealed, unopened original packing)
VOC	20µGr/m ³
TVOC	N/A
PH	7-8°C
Cleaning	Water and Soap
Packing	0.750LT,2.5LT
CHARACTERISTICS	
Characteristics:	.
Can be applied on:	Walls,Wood,Plastic.
for:	Interiors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Roller.
Related products:	DECOR FONDO,TERRA NOSTRA 1 MANO,SP CRAQUE´LEE.

ATTENTION:

- The raw materials used are natural and may have small differences depending on the batches used. It is therefore recommended to use the same batch of product for the same work to be done. Where this is not possible to mix the batches with each other.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com