



TDS 268

INTERIOR - EXTERIOR

TERRE D'ITALIA ROUGE LIGHT

Decorative finish based on black and yellow flocculi in small size with rust final effect.

DESCRIPTION

TERRE D'ITALIA ROUGE LIGHT is a washable decorative finish with rust final effect. The ease of application makes this product suitable for every type of environment and style. Furthermore it is particularly used for decoration of modern style environments.

INDICATIONS FOR USE

- Ensure that the substrate is thoroughly dry. In the case of plaster, ensure that it has a curing time of at least 28 days, depending on the temperature.
- Ensure that the substrate has been well prepared and is suitable for painting: dry plaster, having removed any plaster granules, in case of old walls make sure there are no bad or flourey paints, and remove them if necessary, remove flaking paints, etc.

STEP 1

- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Consult the color chart and choose the desired coloration.
- Apply one or two coats of DECOR FONDO which has to be thinned up to 5-10 % with water.
- Allow to dry 12-24 hours.

STEP 2

- Choose the additive (gold and silver) and the desired color by checking the color chart.
- Mix the product carefully.
- Sand the surface before applying the decorative TERRE D'ITALIA ROUGE LIGHT.
- Apply TERRE D'ITALIA ROUGE LIGHT using the SPALTER tool with alternating movements.
- After 20 min, gently stroke the surface in order to finish the product, by using a stainless steel trowel.
- Allow to dry to appreciate the effect

Stability: 12 Mesi
PH: 7 - 8° C
Voc: 30 gr/l
Specific weight: 1,000

CHARACTERIS: Washable
TOOLS: Spalter 70, Spalter 100, TD Spalter.
DRYING TIME: 6 - 8 hours depending on temperature
STORING = max. temp. + 30° c - min. temp. + 5° c

PACKAGE	PACKAGE PERFORMANCE	REFERRING PERFORMANCE
L 2,5	8 - 9 m ²	1 coat



NOTES

- **N.1** Please note that the Specific Weight indicated may not coincide with the Net Package Weight due to technical coloring reasons

- **N.2** Stability period is purely indicative, it refers to the minimum time of stability of the product if stored in good conditions according to the instructions provided, in the original unopened containers and under appropriate temperature conditions. If stored properly, the product may have stability longer than the minimum recommended period.

- **N. 3** Rivedil warrants that the information in this sheet is provided to the best of its technical and scientific experience and knowledge, however, as elements such as weather conditions, labor, tools, quality of third party products and others, outside the direct control of Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and/or representatives to make any kind of warranty based on the information contained in this document.
It is advisable to always check the actual suitability of the product for the individual specific case. This cancels and supersedes any previous sheet.

- **N. 4** The raw materials used are natural and may have small differences depending on the batches used. It is therefore recommended to use the same batch of product for the same work to be made. Where this is not possible mix batches together.