



TDS 211

INTERIOR - EXTERIOR

## TERRE D'ITALIA ROUGE

Decorative rusted effect finish.

### DESCRIPTION

ROUGE is a new rusted effect decorative paint.

The product, characterized by an extreme ease of application, adapts to any kind of environment or style.

It is widely used for interior decoration within a modern style.

### INDICATIONS FOR USE

- Ensure that the substrate is thoroughly dry. In the case of plaster, ensure that it has a curing time of at least 28 days, depending on the temperature.
- Ensure that the substrate has been well prepared and is suitable for painting: dry plaster, having removed any plaster granules, in case of old walls make sure there are no bad or flourey paints, and remove them if necessary, remove flaking paints, etc.

#### STEP 1

- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Consult the color chart and choose the desired coloration.
- Apply with a brush or roller one or two coats of DECOR FONDO GREY PRIMER diluted with 5-10 % water.
- Allow to dry 12-24 hours.

#### STEP 2

- Prepare ROUGE mixing it with the GOLD or SILVER additive, according to the color chosen in the folder.
- Mix Rouge well with the chosen color and its pearlescent additive.
- Apply ROUGE (ready to use-no need to thin) using SPALTER brush.
- After roughly 20 minutes flatten and fade using a stainless steel trowel.

Stability: 12 Mesi  
PH: 4 - 5° C  
Voc: 10 gr/l  
Specific weight: 1,000

CHARACTERIS: Washable  
TOOLS: Spalter 70, Spalter 100, TD Spalter.  
DRYING TIME: 6 - 8 hours depending on temperature  
STORING = max. temp. + 30° c - min. temp. + 5° c

PACKAGE	PACKAGE PERFORMANCE	REFERRING PERFORMANCE
L 2,5	8 - 9 m <sup>2</sup>	1 coat



## NOTES

- **N.1** Please note that the Specific Weight indicated may not coincide with the Net Package Weight due to technical coloring reasons

- **N.2** Stability period is purely indicative, it refers to the minimum time of stability of the product if stored in good conditions according to the instructions provided, in the original unopened containers and under appropriate temperature conditions. If stored properly, the product may have stability longer than the minimum recommended period.

- **N. 3** Rivedil warrants that the information in this sheet is provided to the best of its technical and scientific experience and knowledge, however, as elements such as weather conditions, labor, tools, quality of third party products and others, outside the direct control of Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and/or representatives to make any kind of warranty based on the information contained in this document.

It is advisable to always check the actual suitability of the product for the individual specific case. This cancels and supersedes any previous sheet.

- **N. 4** The raw materials used are natural and may have small differences depending on the batches used. It is therefore recommended to use the same batch of product for the same work to be made. Where this is not possible mix batches together.