



### **TDS 1005**

**INTERIOR/EXTERIOR** 

| PRODUCT     |   |
|-------------|---|
| DESCRIPTION | : |

# **1970S VINTAGE**

VIBRANT TONE DECORATIVE FINISH

Vibrant "Fluo" decorative paint, applicable as both a finish or a base for SP CRAQUELEE and TERRA NOSTRA CRAQUELEE. Available in the following colors:

- FLUO YELLOW
- FLUO GREEN
- FLUO RED
- FLUO FUCHSIA - FLUO BLUE
- APPLICATION
- Ensure that the surface is suitable for painting and decoration. **INSTRUCTIONS:**

- Make sure the surface is completely dry and clean.

- Apply a coat of SCIK PURAL ACRIL Fixative, diluted 1 to 7.

- Once the fixative is dry, minimum 3 hours, you can proceed with the application of 1970s VINTAGE.

- The product can be applied as is, but to facilitate application, we recommend diluting it by 8-10% with water.

- Apply a first coat with a short nap roller, and wait for it to dry perfectly. 6-8 hours depending on the temperature

- Apply a second coat with a short nap roller, ensuring coverage over the entire surface. At this stage, it is advisable to apply the product as it is.

- Wait 16-20 hours for perfect drying, depending on the temperature.

- Apply the chosen decorative SP CRAQUELEE or TERRA NOSTRA, following the instructions of the chosen products. For both, apply a coat of reactive base, TRANSPARENT SPLITTER (TRASPARENTE SPACCANTE), according to the technical data sheets indicated for these decorative products.

- FLUO YELLOW
- FLUO GREEN
- FLUO RED
- FLUO FUCHSIA
- FLUO BLUE



## **TECHNICAL DATA**

| Binder Nature              | Special resins                           |  |
|----------------------------|--|--|
| Viscosity                  |  |  |
| Drying time                | complete h.                              |  |
| Dilution                   |  |  |
| Yield                      | 8 - 8.5 m²/Lt                            |  |
| Specific weight            | N/A                                      |  |
| Available colors           | YELLOW, GREEN, RED, FUCHSIA, BLUE        |  |
| Applied Appearance:        | Colored, uniform, satin                  |  |
| Packaging Appearance:      | Liquid                                   |  |
| Storage conditions         | Max Temp. °C                             |  |
| Stability                  | 2 years (in original unopened packaging) |  |
| VOC                        | μGr/m³                                   |  |
| тиос                       | N/A                                      |  |
| РН                         | N/A                                      |  |
| Tools cleaning             | Water for tools                          |  |
| Packaging                  | 0.750 LT                                 |  |
| Characteristics            |  |  |
| Characteristics:           | Covering, Ecological                     |  |
| Applicable on:             | Walls                                    |  |
| For :                      | Interior                                 |  |
| Certificate:               | N/A                                      |  |
| Related products and tools |  |  |
|                            |  |  |

| Tools:            | Short nap roller                      |
|-------------------|---------------------------------------|
| Related products: | SP CRAQUELEE, TERRA NOSTRA CRAUQUELEE |

## ATTENTION:

- The raw materials used are natural and may have slight differences depending on the batches used. It is therefore recommended to use the same batch of product for the same job to be carried out. If this is not possible, mix the batches together.

#### NOTE

- No. 1 Please note that the Specific Weight indicated may not coincide with the Net Weight of the packaging for technical reasons related to coloring.

- No. 2 The stability period is purely indicative; it refers to the minimum stability time of the product if stored in good conditions according to the provided instructions, in unopened original containers, and under suitable temperature conditions. If stored properly, the product may have a longer stability period than the recommended minimum period.

- No. 3 Rivedil guarantees that the information in this datasheet is provided to the best of its experience and technical and scientific knowledge. However, since elements such as weather conditions, labor, tools, quality of third-party products, and others are beyond Rivedil's direct control, this document does not constitute a warranty, nor does Rivedil authorize its agents and/or representatives to provide any kind of warranty based on the information contained in this document. It is always recommended to verify the actual suitability of the product for the specific case. This document cancels and replaces any previous datasheets.