



TDS 131

INTERIOR/EXTERIOR

SCUDO I

Protective resin for OXYDA and finishes before the application of SCUDO.

PRODUCT DESCRIPTION :

SCUDO I is a protective resin that prevents color alteration in absorbent coatings. The use of SCUDO I becomes necessary when it is required to protect a substrate with POLYURETHANE SHIELD after applying a decorative finish or plaster (for example OXYDA.).

If SCUDO I is not applied, the protective coating based on polyurethane resins could create a wet effect on the substrate, thus altering its original color.

Applying SCUDO I means protecting the color of the substrate (which remains unchanged and maintains its uniformity), avoiding this phenomenon.

APPLICATION INSTRUCTIONS:

- Apply a decorative product from the Rivedil line to the desired surface following the instructions described in the technical data sheet.

- After 24-48 hours, once the applied decorative product (OXYDA, SINFONIA, PERSIA...) has completely dried, apply SCUDO I using a short-haired roller. Proceed with circular movements on the surface by using a paper towel, it will promote absorption. Ensure to cover the entire surface and apply the correct amount without leaving excess product residues. Alternatively, it can be applied directly with a sponge, spreading the product in a circular movements on the surface so that SCUDO I penetrates into all the pores.


- Allow to dry for 12-24 hours depending on temperature.



TECHNICAL DATA

Binder Nature	Vinyl Copolymer
Viscosity	
Drying time	1/2 hour to the touch, 6-12 hours complete
Dilution	Ready to use
Yield	20-23 m ² /Lt depending on the substrate
Specific weight	1 Kg/Lt
Available colors	Transparent
Applied Aspect	Matt transparent
Aspect in Packaging	Liquid transparent
Storage conditions	Max Temp. +30°C, Min Temp. +5°C
Stability	2 (in original unopened packaging)
VOC	10µGr/m ³
TVOC	N/AµGr/m ³
PH	8-9°C
Tools cleaning	Water and Soap
Packaging	0.750LT, 2.5LT, 10LT

Characteristics

Characteristics:	Washable
Applicable on:	Walls, Floors, Work Surfaces, Bathrooms.
For :	Interior and Exterior
Certificate:	

Related products and tools

Tools:	Roller, Brush, Spray.
Related products:	OXYDA PRIMER

NOTE

- No. 1 Please note that the Specific Weight indicated may not coincide with the Net Weight of the packaging for technical reasons related to coloring.

- No. 2 The stability period is purely indicative; it refers to the minimum stability time of the product if stored in good conditions according to the provided instructions, in unopened original containers, and under suitable temperature conditions. If stored properly, the product may have a longer stability period than the recommended minimum period.

- No. 3 Rivedil guarantees that the information in this datasheet is provided to the best of its experience and technical and scientific knowledge. However, since elements such as weather conditions, labor, tools, quality of third-party products, and others are beyond Rivedil's direct control, this document does not constitute a warranty, nor does Rivedil authorize its agents and/or representatives to provide any kind of warranty based on the information contained in this document. It is always recommended to verify the actual suitability of the product for the specific case. This document cancels and replaces any previous datasheets.